

ENSTO

SR1

SR1 Joint compound

Code SR1

GTIN 6418677405402

ENumber

Name SR1 Joint compound
Joint compound

Description SR1 is used to prevent oxidation on aluminium surfaces. The use of the wire brush and joint compound SR1 reduces the transition resistance. It also protects the connection from corrosion. Used for SL, SM and KG connectors and aluminium, steel and copper conductors

EAC



Technical specification

Dimensions

Weight: 0.225 kg

Features

For connector: SLxx, SMxx, KGxx

Ratings

ETIM 7: EC002757 Lubricant

Specification

Use: SR1 is lithium based grease which contains oxidation and corrosion preventing chemicals and is used on brushed aluminium surfaces to prevent oxidation and corrosion. Brushing and greasing lowers the contact surface resistance. Can be used indoors and outdoors and is compatible with copper connections. Prolonged or recurring skin contact can cause dryness, irritation and infections of the skin.

Construction:

Construction:**TYPICAL CHARACTERISTICS**

Base oil viscosity cSt / 40 °C	112
Base oil viscosity cSt / 100 °C	10
Liquefaction point °C	>180
Usable in temperature range of °C	-30...+110
NLGI-class	2
Coagulant type	Litium
SKF Emcor WWO distilled water /ISO 11007mod	0-0
Copper corrosion 24h/100°C/ASTM D4048	1b
Oil separation 168h/40 °C/IP 121	6%

Markings:

SR1, Ensto

Standard:

Connector grease DIN 51502 K2K-30 ISO 6743 ISO-L-XCCHA2

ETIM**ETIM**

Can be used on plastic:	true
Can be used on metal:	true
Can be used on concrete:	true
Suitable for tubes:	true
Suitable for cables:	true
Acid-free:	true
Net weight:	225 g
Can be used on wet surface:	true
Shape:	Gel
Packaging:	Tube
Suitable for potable water:	true

Packaging**Default package**

Unit:	PCS
Size:	25
Length:	385 mm
Width:	260 mm
Height:	165 mm
Weight (net):	6.35 kg
Weight (brt):	6.6 kg

Volume:	0.0165
---------	--------

Pallet package

Unit:	PCS
Size:	1350
Length:	1200 mm
Width:	800 mm
Height:	1140 mm
Weight (net):	342.9 kg
Weight (brt):	363 kg
Volume:	1.0944