



Saves Your Energy

PRODUCT CARD

11/1/16

SV29.2511

Fuse fixture

Kód SV29.2511
 GTIN 6418677432835
 Název Fuse fixture
 SV29.25 25A and SL11.11 (Al 10-95 / Cu 1.5-70)
 Popis The SV29.2511 includes connector SL11.11 and fuse fixture SV29.25. Fuse fixture is without the diazed screw adapter.



Technické parametry

Dimensions

Weight: 0.32 kg
 Conductor size Cu: 1.5 ... 10 mm²

Electrical values

Fuse max.: 25 A

Features

Connectors included: SL11.11
 Fuse contact: Diazed screw adapter not included

Ratings

ETIM: EC000899

ETIM

ETIM

Colour: Black
 Mounting method: Direct mounting
 Nominal rated voltage: 230 V
 Connectable conductor cross section fine-strand without cable end sleeve: 1.5 ... 95 mm²
 Rated current I_n: 25 A
 Type of electrical connection 1: Insulation piercing connection
 Connection position: Sideways
 Material insulation body: Thermoplastic
 Type of fuse insert: D-system

| | |
|----------------------------------|------------------|
| Type of fuse holder: | Screwable |
| Type of electrical connection 2: | Screw connection |

Balení

Balení

| | |
|---------------|-----------|
| Size: | 10 |
| Length: | 385 mm |
| Width: | 266 mm |
| Height: | 165 mm |
| Weight (net): | 3.21 kg |
| Weight (brt): | 3.4581 kg |
| Volume: | 0.0165 |

Pallet package

| | |
|---------------|-----------|
| Size: | 540 |
| Length: | 1200 mm |
| Width: | 800 mm |
| Height: | 1140 mm |
| Weight (net): | 184.68 kg |
| Weight (brt): | 205 kg |
| Volume: | 1.0944 |

